



WRPTA SERIES

Brown polyurethane tyre on aluminium rim.

Hardness: 95±2 Shore A

Temperature range: -20°C to +80°C

Wheel diameter (mm)	Tread width (mm)	Bore size (mm)	Hub length (mm)	Ball journal bearing
100	50	20	50	BZMH100WRPTABJM20 350kg
			56	BZH100WRPTABJM20 350kg
125	50	20	56	BZH125WRPTABJM20 450kg
150	50	20	56	BZH150WRPTABJM20 575kg
200	50	20	56	BZH200WRPTABJM20 775kg

Wheel diameter (mm)	Tread width (mm)	Bore size (mm)	Hub length (mm)	Ball journal bearing
100	50	20	50	BZMH100WRPTABJM20 350kg
			56	BZH100WRPTABJM20 350kg
125	50	20	56	BZH125WRPTABJM20 450kg
150	50	20	56	BZH150WRPTABJM20 575kg
200	50	20	56	BZH200WRPTABJM20 775kg

100 to
200mm

350 to
775kg

ERGONOMIC WHEELS

New ergonomic design wheels for effortless rolling with very low push-pull effort required to move loads. Generous amount of polyurethane is mechanically locked and chemically bonded to a metal core, ensuring excellent performance in the most demanding conditions.

